


# ENTRANCE QUOTE REQUEST FORM

Customer: \_\_\_\_\_ Job Name: \_\_\_\_\_  
 Contact: \_\_\_\_\_ Location: \_\_\_\_\_  
 Phone: \_\_\_\_\_ Cell: \_\_\_\_\_ Required Ship Date: \_\_\_\_\_  
 Fax: \_\_\_\_\_ Shipping Address: \_\_\_\_\_  
 E-mail: \_\_\_\_\_

## Project Data

Capacity: \_\_\_\_\_  
 Class: \_\_\_\_\_  
 Code: \_\_\_\_\_  
 Total Travel: \_\_\_\_\_  
 Fascia Required  Yes  No  
**Industry Standard Door Hand =**  
**CLOSING Direction Looking From**  
**HALLWAY**



**Door Hand**  
**Above Cab View**

## Specific Floor to Floor Distance

9	18
<input style="width: 100%;" type="text"/>	<input style="width: 100%;" type="text"/>
8	17
<input style="width: 100%;" type="text"/>	<input style="width: 100%;" type="text"/>
7	16
<input style="width: 100%;" type="text"/>	<input style="width: 100%;" type="text"/>
6	15
<input style="width: 100%;" type="text"/>	<input style="width: 100%;" type="text"/>
5	14
<input style="width: 100%;" type="text"/>	<input style="width: 100%;" type="text"/>
4	13
<input style="width: 100%;" type="text"/>	<input style="width: 100%;" type="text"/>
3	12
<input style="width: 100%;" type="text"/>	<input style="width: 100%;" type="text"/>
2	11
<input style="width: 100%;" type="text"/>	<input style="width: 100%;" type="text"/>
1	10
<input style="width: 100%;" type="text"/>	<input style="width: 100%;" type="text"/>

	Max Width	Max Height		Max Width	Max Height
1SSO	42"	96"	1SCO	50"	96"
	Max Width	Max Height		Max Width	Max Height
2SSO	84"	96"	2SCO	96"	96"


Configuration Doors Drilled For GAL	Standard Opening Size (wide x tall)	# Entrance Openings
1SSO - Right hand	36" x 84"	_____
	42" x 84"	_____
1SSO - Left hand	36" x 84"	_____
	42" x 84"	_____
1SCO	42" x 84"	_____
	48" x 84"	_____
2SSO - Right hand	42" x 84"	_____
	48" x 84"	_____
2SSO - Left hand	42" x 84"	_____
	48" x 84"	_____
2SCO	60" x 84"	_____
	72" x 84"	_____

(Custom Application) Please complete the shaded area for any NON standard Door Size		
Configuration / Operator	Opening Size	# Entrance Openings

<b>Standard Finish's</b>			#4 (304) SS
WHITE	CREAM (RAL9001)	LIGHT IVORY (RAL1015)	ALLADIN BLUE
BLACK	AGATE GREY (RAL7038)	STONE GREY (RAL7030)	TARPAULIN GREY (RAL7010)
<b>Non Standard Finish's - Longer Lead Time:</b>			OTHER <input type="checkbox"/>
#4 (316) SS	#8 (304) SS	SSM RIMEX	_____
Door Finish _____	Frame Finish _____		

**Sill Finish:**  Aluminum  Nickel Silver  Stainless Steel  GROUDED  Yes  No

**Emer. Keyhole Type - ENTRANCE ONLY**  
 (Select all that apply with quantity)  
 None  Key Hole Only  Escutcheon Tube  Trilock  
 Qty: \_\_\_\_\_

**Center Opening Only - Keyhole Hand Location**  
 ENTRANCE ONLY (Select ONE)  
 Left Hand   Right Hand  
 Viewing from hallway into car.

**Sound deadening mastic**  
 All doors

**Door Skin Thickness**  
 20 Ga (Standard)  16 Ga (NON Standard)

**Additional Options**  
 Jamb Braille by MEI  
 Jamb Braille Marking \_\_\_\_\_  
 Self Adhesive  
 Pin Mount - Drilling in Field by Others  
 Stud Mount - Drilling in Field by Others

**Sound deadening mastic (Select one)**  
 All Frames

**Frame Material Thickness**  
 16 Ga (Standard)  14 Ga (NON Standard)

**Entrance Wall Material**  
 Gypsum  
 CMU / Concrete  
 Gypsum & CMU / Concrete  
 Entrance Wall Thickness \_\_\_\_\_  
 \*Please Specify Each Landing Thickness if Different

Standard Notes:  
 Frames: Enamel - cold rolled A-1 088, (2" square profile) Bolted  
 Doors: 16 ga cold rolled steel construction wrapped with 20 ga stainless  
 Fascia: 14ga Galvaniel - Header: 10 ga steel enamel - Struts: 10 ga steel enamel  
 Frame cut outs to be done in field on site by others